

32 OZ. 1 GAL. 5 GAL.

HYDRO-BALANCE



OEM APPROVED

P-22032, P-22001, P-22005

HEALTH & SAFETY

Avoid prolonged or repeated contact with skin or clothing. If product gets in eyes, flush with water for 15 minutes. If irritation persists, consult a physician. Wash hands with soap and water after use. Read entire label and **Safety Data Sheet** before use.



Made in U.S.A.
HYDRO-BALANCE CORP.
 519 Huffines Blvd., Lewisville, TX U.S.A.
 (800) 527-5166 (972) 394-9422
www.HydroBalance.com

ISO VG 220

OEM APPROVED

SYNTHETIC ESTER REFRIGERATION LUBRICANT

ISO 220

For Use with Environmentally Sound HFC Refrigerants

- Excellent Lubricating Properties Over a Wide Temperature Range
- Superior Corrosion Resistance
Excellent Oxidative and Hydrolytic Stability
- Good Load Carry Capabilities
- Excellent Retrofit Capabilities

HYDRO-BALANCE ISO SERIES

Polyol-Ester based refrigeration lubricants are specifically formulated for use with environmentally friendly HFC refrigerants. They are also suitable with HCFC and CFC refrigerants which make them suitable for many applications.

TYPICAL COMPRESSOR APPLICATIONS

ISO 220 is used in screw compressors of industrial and commercial chillers and A/C packages utilizing HFC refrigerants.







Contents of this container are manufactured by leading producers of Polyol-Ester refrigeration lubricants and meet the specifications of many equipment and compressor manufacturers. Always consult your manufacturer for specific applications.

NOTE: Refrigeration lubricants absorb moisture from the air. This container is packaged under dry nitrogen to maintain product integrity. Keep container tightly sealed until time of use and when not dispensing.

Hydro-Balance Lubes



POLYOL ESTER LUBRICANTS

- Excellent lubricating properties over a wide temperature range
- OEM Approved
- Specially formulated for use with HFC refrigerants

DESCRIPTION	ITEM #	CONTAINER	VISCOSITY SUS @ 100°F	ISO VISCOSITY GRADE	REPLACES
ISO 32, SYNTHETIC ESTER	P-3232 P-3201	32-OUNCE 1-GALLON	150 SUS		RL 32H EAL 32
ISO 32 3MAF, SYNTHETIC ESTER (COPELAND APPROVED)	P-323MAF32 P-323MAF01	32-OUNCE 1-GALLON	150 SUS		RL32 3MAF
ISO 68, SYNTHETIC ESTER	P-6832 P-6801	32-OUNCE 1-GALLON	300 SUS		SW 68 RL 68HB
ISO 68S, SYNTHETIC ESTER	P-E6832 P-E6801	32-OUNCE 1-GALLON	300 SUS		ICEMATIC E68 RL 68H EAL 68
ISO 100, SYNTHETIC ESTER	P-E10032 P-E10001	32-OUNCE 1-GALLON	500 SUS		ICEMATIC E100 RL100E
ISO 220, SYNTHETIC ESTER	P-22032 P-22001	32-OUNCE 1-GALLON	1100 SUS		SW 220 RL 220HC+




MINERAL LUBRICANTS

- High quality naphthenic based lubricants
- OEM approved
- Compatible with CFC and HCFC refrigerants
- Moisture and wax free
- Filtered to 1 micron for high purity


MINERAL REFRIGERATION OIL #3 (COPELAND APPROVED)	H-2301 H-2305	1-GALLON 5-GALLON PAIL	150 SUS		3GS, C-3, R0-15, WF 32
MINERAL REFRIGERATION OIL #4	H-2401 H-2405	1-GALLON 5-GALLON PAIL	300 SUS		4GS, C-4, R0-30, WF 68

ALKYLBENZENE LUBRICANTS

- High quality reliable lubrication
- High solubility ~ Low foaming ~ Low floc point
- Excellent thermal stability
- OEM approved
- Compatible with CFC & HCFC refrigerants and mineral oils

Z-150 ALKYL BENZENE REFR. OIL	Z-150 01	1-GALLON	150 SUS		ZEROL 150 RF 150 AB 150 ROYCO 2032
Z-200CX ALKYL BENZENE REFR. OIL (COPELAND APPROVED)	Z 200 01	1-GALLON	200 SUS		ZEROL 200TD AB 200A
Z-300 ALKYL BENZENE REFR. OIL	Z 300 01	1-GALLON	300 SUS		ZEROL 300 AB 300

SPECIALTY PRODUCTS

DUAL-PURPOSE VACUUM PUMP OIL	H-2601 H-2600	1-GALLON 32-OUNCE			VIRGINIA KMP NU-CALGON JB, ROBINAIR, ETC.
PVE 68 POLYVINYL ETHER	H-PVE6832	32-OUNCE			VG 68 PVE
LUBRI-TECT™ NEUTRALIZES, SCAVENGES, PREVENTS ACID AND MOISTURE IN A/C AND REFRIGERATION SYSTEMS	H-3702	2.4 FL OZ			ACID AWAY ACID SCAVENGER ACID NEUTRALIZERS