

## **Pre-Clean** Coil & Component Parts Cleaner



### **KEY FEATURES**

H.V.A.C. System Cleaner Leaves No Residue

Use Prior to Application of Anti-Foulant Treatment Such as Coil & Duct Spray (H-9501)

Sprayer Refill, Odor Control

# NAKES UP TO

Part #	Product	QTY	Size
H-PC01	Evap. Cleaner	4	1 Gal Bottle



#### Directions For Use: DANGER: Causes severe skin burns and eye damage. Window Units, Small Central Units: Do not breathe mist/vapors/spray. Wash face, hands, and any exposed 1. Dilute with at least 4 parts water. skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. 2. Shut unit off 3. Spray coil thoroughly using enough liquid to cause contamination to run off coil. 4. Turn on blower to reduce drying time. FIRST AID: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. 5. Apply Ever-Clean Cooling Coil Anti-Foulant(H-9901 or H-9932) for increased indoor air Rinse skin with water/shower. Wash contaminated clothing before quality (IAQ) protection. reuse. IF INHALED: Remove person to fresh air and keep comfortable for **Commercial Systems, Air Handling Units:** breathing. IF IN EYES: Rinse cautiously with water for several minutes. Dilute with at least 4 parts water. If possible leave air flow on during application. Spray Remove contact lenses, if present and easy to do. Continue rinsing. intake side of coil with coarse spray until saturated to the run-off point (Suction of system Immediately call a POISON CENTER/Doctor. will cause complete coil penetration). Refuse and contamination will drain as condensate. If it is not possible to leave air flow on during application, spray coil thoroughly and turn air on immediately after application. Store locked up. Dispose of contents and container in accordance with all local, regional, and national Pre-Clean should also be used on other system components such as blowers, housings, regulations. baffles, condensate pans and sheet metal duct work. Remove loose lint and particulate Contains [CAS]: Sodium metasilicate [6834-92-0], alcohol ethoxy with brush or vacuum and spray or swab solution on surfaces to be treated. Rinse or wipe contaminated cleaning solution, allow to dry throughly. Apply Ever-Clean Cooling Coil Anti-Foulant(H-9901 or H-9932) for increased indoor air quality (IAQ) protection.







### HYDRO-BALANCE CORPORATION 519 HUFFINES BLVD. LEWISVILLE, TX 75056 (800) 527-5166 | (972) 394-9422 HydroBalance.com