

PVE68

Polyvinyl Ether Refrigeration Lubricant

LUBRICANT



VISCOSITY



KEY FEATURES

For Use in Systems Requiring Polyvinyl Ether Lubricant

Compatible with all HFC refrigerants.

Does not hydrolyze to form acid

Exceptional resistance to capillary tube blockage

Excellent lubricity for greater wear protection

Meets or exceeds OEM specifications

Part #	Product	QTY	Size
H-PVE6801	Refrigeration Oil	4	1 Gal Cans
H-PVE6805	Refrigeration Oil	1	5 Gal Pail



Hydro-Balance® PVE 68 is a new generation polyvinyl ether compressor lubricant for use with HFC refrigerants. Polyvinyl ether based lubricants are inherently resistant to hydrolysis which provides superiority over polyol esters (POE).

Hydro-Balance PVE 68 is for use in systems requiring ISO VG 68 polyvinyl ether lubricant and replaces FVC68D. Where approved by the OEM, HYDRO-BALANCE PVE 68 is also suitable for systems requiring ISO VG 32 polyvinyl ether lubricant.

Always consult equipment/compressor manufacturer for proper lubricant selection.

Refrigeration lubricants absorb moisture from the air. This container was packaged under dry nitrogen to preserve product integrity. Always keep container tightly closed unless dispensing.

Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.

WARNING: Suspected of damaging fertility or the unborn child. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye protection.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation develops or persists, get medical attention. IF Inhalation: Remove person to fresh air if adverse effects are observed. IF Skin contact: Wash with soap and water. IF Ingested: Do not induce vomiting. Rinse mouth. Get medical attention if symptoms occur.

