

POE32

Polyvinyl Ether
Refrigeration Lubricant

LUBRICANT



VISCOSITY



KEY FEATURES

For Use with Environmentally Sound HFC Refrigerants

Excellent Lubricating Properties Over a Wide Temperature Range

Superior Corrosion Resistance, Plus Excellent Oxidative and Hydrolytic Stability

Good Load Carry Capabilities & Excellent Retrofit Capabilities

Part #	Product	QTY	Size
P-3201	Refrigeration Oil	4	1 Gal Cans
P-3205	Refrigeration Oil	1	5 Gal Pail



Hydro-Balance ISO Series

Polyol-Ester based refrigeration lubricants are specifically formulated for use with environmentally friendly HFC refrigerants. They are also suitable with HCFC and CFC refrigerants which make them suitable for many applications.

Typical Compressor Applications

ISO 32 is for use with systems requiring ISO Viscosity Grade 32 polyol ester lubricant.

Health & Safety

Avoid prolonged or repeated contact with skin or clothing. If product gets in eyes, flush with water for 15 minutes. If irritation persists, consult a physician. Wash hands with soap and water after use. Read entire label and Safety Data Sheet before use.

Contents of this container are manufactured by leading producers of Polyol-Ester refrigeration lubricants and meet the specifications of many equipment and compressor manufacturers. Always consult your manufacturer for specific applications.