

# Z-150

## Alkylbenzene Refrigeration Oil

LUBRICANT



VISCOSITY



### KEY FEATURES

**Meets Specifications Of Many Compressor And Equipment Manufacturers**

**@100°F 150 SUS**

**Excellent Compatibility, Low Floc Point, Reliable Lubrication, High Solubility, Low Foaming, Excellent Thermal Stability**

Part #	Product	QTY	Size
Z-150 01	Alkylbenzene Oil	4	1 Gal Bottles



Z-150 is recommended for use with HCFC and CFC refrigerants in applications requiring a 150 SUS (ISO VG 32) alkylbenzene compressor lubricant. Do NOT use in systems with HFC refrigerants such as R134a and R410a. **Always follow the equipment manufacturer's recommendation for selection.**

**CAUTION:** Keep out of reach of children. For professional use only. Read Safety Data Sheet and entire label before use.

**FIRST AID:** Wash skin contact thoroughly with soap and water. Flush eyes with water for 15 minutes. Get medical attention if irritation develops. Avoid repeated and prolonged contact.

**NOTE:** Refrigeration lubricants absorb moisture from air which may be harmful to equipment. Keep container tightly closed when not dispensing.