

Z-300

Alkylbenzene Refrigeration Oil

LUBRICANT



VISCOSITY



KEY FEATURES

Meets Specifications Of Many Compressor And Equipment Manufacturers

@100°F 300 SUS

Excellent Compatibility, Low Floc Point, Reliable Lubrication, High Solubility, Low Foaming, Excellent Thermal Stability

Part #	Product	QTY	Size
Z-300 01	Alkylbenzene Oil	4	1 Gal Bottles



Z 300 is recommended for use with refrigerants R-401a/R-401b and R-402a/R-402-b, as well as other HCFC and CFC refrigerants in field service and retrofit applications. Z 300 can also be used for the initial flush in HFC retrofits. **Always follow the equipment manufacturer's recommendation for selection.**

CAUTION: Keep out of reach of children. For professional use only. Read Safety Data Sheet and entire label before use.

FIRST AID: Wash skin contact thoroughly with soap and water. Flush eyes with water for 15 minutes. Get medical attention if irritation develops. Avoid repeated and prolonged contact.

NOTE: Refrigeration lubricants absorb moisture from air which may be harmful to equipment. Keep container tightly closed when not dispensing.